

TECHNICAL DATA SHEET

TDS 1829 KB 01/16 V2

CRAIG & ROSE

∞ SINCE 1829 ∞

1829 KITCHEN & BATHROOM PAINT

TYPE OF MATERIAL	A water based Kitchen and Bathroom Paint with a soft sheen finish. Made with pure Acrylic resin, Titanium Dioxide and other selected additives to reduce the likelihood of biological contamination.
USES	A high quality, water resistant paint with a soft sheen specifically designed for use on walls ceilings and woodwork in kitchens and bathrooms. It has good resistance to water splashes and attack by moulds and exhibits better adhesion than vinyl silk emulsion, but without the solvent fumes of oil based eggshell paints. Not suitable for use in areas subject to direct water e.g. within a shower area.
COLOURS AVAILABLE	Selected colours only
FINISH	Soft Sheen
NUMBER OF COMPONENTS	One
METHOD OF APPLICATION	Brush or Roller –
PRACTICAL COVERAGE PER LITRE	10-12 sq M / Ltr,
WET FILM THICKNESS RANGE	60 – 75 microns
DRY FILM THICKNESS RANGE	20 – 25 microns
FLASH POINT	N/A Water based.
DRYING TIMES: SURFACE HARD OVERCOATING	1-2 Hours 2-4 Hours 5 Hours Leave to dry for 48 hours after the final coat before subjecting the room to condensation.
CLEANING SOLVENT	Water
APPLICATION INSTRUCTIONS	Apply 2 coats by brush or roller (synthetic bristle brushes give good

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

TECHNICAL DATA SHEET

TDS 1829 KB 01/16 V2

CRAIG & ROSE

∞ SINCE 1829 ∞

1829 KITCHEN & BATHROOM PAINT

	<p>results). Previously painted gloss or lustre surfaces should be abraded to improve adhesion. See can for further details.</p> <p>Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood or metal as they may contain harmful lead. For further advice, please contact the British Coatings Federation Ltd, James House, Bridge Street, Leatherhead. KT22 7EP.</p>
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	<p>Do not apply to radiators or surfaces that are likely to become hot. Ensure the previous coat is completely dry before over coating. Do not apply in temperatures near freezing, as this will seriously slow down the drying and may destroy the structure of the paint. Store in a frost-free place and do not allow the paint to freeze.</p>
SAFETY PRECAUTIONS	<p>Read the can label.</p> <p>After contact with skin, wash immediately with plenty of soap and water. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. See Craig & Rose Safety Data Sheet.</p>
PRODUCT CONTAINS BIOCIDES FOR THE PROTECTION OF THE PAINT FILM.	<p>Contains: Benx, Methyl,Chloromethyl Isothiazolone & Octyl-Isothiazolone.</p> <p>May produce an allergic reaction.</p>
VOC CONTENT VOLATILE ORGANIC COMPOUNDS MAY CAUSE HARM TO THE ENVIRONMENT	<p>EU Limit value for this product (Cat A/a : 30g/L)</p> <p>This product contains max : 3g/L VOC.</p>
DISPOSAL CONSIDERATIONS	<p>Do not empty into drains or watercourses. Dispose of contents/containers in accordance with local regulations.</p>

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.