

TECHNICAL DATASHEET



ARTISAN EVO

Digital Electric Thermostatic Mixer Shower with Ceiling Fed Shower Rose

Product Specification

Product Codes & Finishes:	ARDE SHCCF W (White) ARDE SHCCF B (Black)
Product Type:	Contemporary
Construction:	Plastic (ABS)
Electricity Supply:	230V AC/ 35W
Supply:	Suitable for high pressure systems (Preferably balanced)
Inlet Connections:	½" BSP with 70mm between centres
Outlet Connections:	½" BSP
Working Pressures:	Min 0.5bar, Max 5.0bar – For optimum performance a minimum pressure of 1 bar is required.



Additional Information

- Easy to install and use. Operated by push buttons and a single on/off lever.
- Digital temperature control and display. Error codes will be displayed here if there is a problem with the shower
- Time-Out setting – if the shower has been running for 30mins, the mixing valve will automatically shut-off to save water and energy. Normal use will resume once the handle has been returned to the 'Off' position
- Four flow settings, eco, low, medium & high.
- Low battery indicator.
- Wireless controller can be positioned up to 10 metres from the mixing valve.
- Supplied with large 200mm ceiling fed shower rose and 2x AA Batteries.
- Temperature factory set to a maximum of 48oC, can be over-ridden to suit user preference

Compliance / Approvals

BEAB Certificate No:	21536
WRAS:	1603029
CE Mark:	

Technical Advice: For further information please call 0844 7016273 or email customer@bristan.com

Guarantee: 5 years covering manufacturing faults.

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG
Telephone: 0844 701 6274 Facsimile: 0844 701 6275
Web Site: www.bristan.com Email: enquire@bristan.com



The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.


TECHNICAL DATASHEET



ARTISAN EVO

Digital Electric Thermostatic Mixer Shower with Ceiling Fed Shower Rose


Dimensions (mm)



Flow Rates (litres per minute)

Flow Setting	Eco (0.5 Bar)	Low (1.0 Bar)	Medium (2.0 Bar)	High (3.0 Bar)
Through Shower Rose	5.27	7.45	10.53	12.9

Quoted as per European Water Label (EWL) scheme conditions:
Output = 42°C; Input = 15°C; Voltage = 240V



Technical Advice:

For further information please call 0844 7016273 or email customercare@bristan.com

Guarantee:

5 years covering manufacturing faults.

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG
Telephone: 0844 701 6274 Facsimile: 0844 701 6275
Web Site: www.bristan.com Email: enquire@bristan.com



The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.