

TECHNICAL DATA SHEET

CARRE

Thermostatic Surface Mounted Shower Valve with Diverter and Fast Fit Connections

Product Specification

Product Code:	CR SHXDIVFF C
Finish:	Chrome
Product Type:	Contemporary
Construction:	Body is of Brass construction
Cartridge Type:	Thermostatic Cartridge
Supply:	Suitable for all plumbing systems
Inlet Connections:	15mm Compression Connections
Outlet Connection:	G 1/2"
Working Pressures:	Min 0.5 bar Max. 5.0 bar
Dimensions for Fitting:	150mm inlet centres

Additional Information

- Chrome plated to BS EN 248
- Dual Control – flow and temperature are controlled separately giving accurate control of both
- Thermostatic cartridge maintains showering temperature to +/- 1oC giving a stable outlet temperature
- Automatic shut-off in the event of hot or cold water supply failure to prevent scalding
- Temperature factory set to a maximum of 38oC to eliminate the ability to select and unsafe temperature. Can be over-riden to a maximum of 46oC
- Supplied with a 1.5m hose, 200mm shower rose, and single function handset; both with rub-clean nozzles.
- Utilises a unique fast-fit system with WMNT10 C



Flow Rates (litres per minute)

System Pressure	0.5bar	1.0bar	2bar	3.0bar	4.0bar	5.0bar
Through Shower Rose	6.2	8.78	12.41	15.2	17.55	19.62
Through Handset	6.08	8.6	12.17	14.9	17.21	19.24

Compliance / Approvals

WRAS Approval No: 1503001

Technical Advice: For further information please call 0844 7016273 or email customercare@bristan.com

Guarantee: 5 years covering manufacturing faults.

